

TECHNICAL DATA

UPDATE: 2021/12/01

PRODUCT TYPE: AL-MH(6515)

PRODUCT NAME: Semigloss/6515/58g white glassine liner

FACESTOCK: SPEC.:

White semigloss paper. WIDTH: 1070 MM/1230MM/1530MM

GB/T451.2 Weight: 80 ± 3 g/m^2 **Printability:**

Thickness: $0.068 \pm 0.003 \text{ mm}$ GB/T451.3 Suitable for a variety of ways of printing mono

chrome and color printing, the printing ink has

materials have excellent adhesion effect.

Widely used in food, advertising and drug labe

a good performance.

I, etc.

Application: Products can has good adhesiveness, on many

Permanent, hot-melt pressure sensitive adhesive.

Initial Tack 8# GB/T 4852 Shelf life:

180° Peel Adhesion GB/T 2792 The durability of this product is one year, 12 N/25mm

stored at $23 \pm 2^{\circ}$ C \ reality humidity $60 \pm 5\%$,

5°C Min. Application Temp. avoid direct sunlight.

Service Temp.

Liner

Adhesive:

Uses instruction: White glassine release paper

-10℃~60℃

The above typical technical data are given Weight: 58 ± 3 g/m² GB/T451.2 based upon experimental testing result (only GB/T451.3 Thickness: $0.050 \pm 0.005 \, \text{mm}$

for reference). The material should be tested thoroughly under end-use conditions to ensure they meet the requirements of the specific application or notice our business department to provide future clarification or service. As the products are used outside of our control we can not responsibility for any damage which may be caused using the

product. We reserve the right to modify the technical specification without prior notice.

convertidoracolormake.com

🐚 +52 446 184 6629 🔃 ventasl@convertidoracolormake.com

