

Product Technical Data Sheet

Semi Gloss Art Paper/acrylic/60g White Glassine

Facestock

Semi Gloss Art Paper/

Thickness(mm) 0.078±0.003
Basis Weight 80g/m2
Color white

Adhesive

Water based glue

Liner

Glassine release paper

Thickness(mm) 0.058 ± 0.005 Basis Weight 60 ± 2 g/m2 Color White Transparency 52%

Test Project	Characteristic Value	Unit	Test Method
Spread	20±3	g/ square meter	
Adhesive Force	$0.9\uparrow$	Kn/m	GB/T 2792
Initial Bonding Strength	9	#	GB/T 4852
Endurance Bonding Strength	5	Hours	GB/T 4851
Application Temperature	-40~80	degree celsius	

Shelf life

24 Month if stored at 22°C and 50% relative humidity

1. Best printing processing environment: temperature 22 ± 3 degree celsius, humidity 55 % \pm 5.

Precautions for Use:

- 2. When use, please try to be affixed to the surface to remove dirt, oil, water and other impurities.
- 3. Subjected to an appropriate pressure on the tape, square can achieve sufficient adhesion strength.

Remark:

All above-mentioned technical information has been recognized as the company uses reliable testing methods, the resulting is an average value after repeated testing, but to ensure the proper selection and use of our products, please basing on the object when you use, firstly use of the purposes and conditions detailed understanding of the trial, or notify us in order to provide you further instructions and services.

Version The first edition **Revision date** 2022-4-16











